

MY SPECIAL

14 - 15

16


MY SPECIAL 14 engine with 12,2 hp, diesel

MY SPECIAL 15 engine with 13,6 hp, diesel



KEY

the speeds are given in kph



My Special Series, versatile and easy to manoeuvre.

With 12 to 14 hp diesel and gasoline engines, the My Special series two-wheeled tractors are extremely versatile and simple to manoeuvre when equipped with various tools. They are easily able to deal with all the cutting, ploughing, planting, mowing and pest control treatments required in greenhouses, nurseries and market gardens. If these are the versatility features of My Special, we've certainly not neglected the technical aspect or safety, thus the operator can work with the utmost confidence. 6-speed gearbox with 4 forward and 2 reverse speeds. Two power take-offs, two cutting speeds for each speed gear, lower power take-off synchronized with all the ground speeds of the machine, reverse speed inclusive.

Easy to handle

Series MY SPECIAL

MY SPECIAL 14

MY SPECIAL 15

Engine		Series MY SPECIAL	
Type		Diesel Lombardini 3LD510	Diesel Lombardini 25LD330/2 BI
Power rating	Kw/Ch	9 (12,2)	10 (13,6)
N° cylinders / nominal rate		1 / 3000 rpm	2 / 3000 rpm
Swept volume	cc.	510	654
Start		pull start; electrical starting optional	pull start; electrical starting optional
Tank capacity	Lt.	5,2	4
Transmission			
N° speeds		4 FWD + 1 REV	4 FWD + 1 REV
Main clutch		dry-disk	dry-disk
Differential lock		yes	yes
Wheels clutch release		-	-
Speed	Kph	FWD: 1,37 / 2,77 / 6,0 / 8,0 REV: 2,81	FWD: 1,37 / 2,77 / 6,0 / 8,0 REV: 2,81
Reverse gear block (safety device)		yes	yes
Brakes			
Type of brakes		band type	
PTO			
Type		with 2 speeds independent from the tractor's ground speed (540 rpm - 900 rpm)	
Reverse gear block when PTO is engaged (safety device)		yes	
Driver's Area			
Handlebars		fixed, sheet made, height adjustable in 9 positions.	fixed, sheet made, height adjustable in 9 positions.
Capot		sheet	sheet
Tow hook		yes	yes
GEAR STOP safety device		yes	yes
Coupling system for attachments		fixed	fixed
Weights and Dimensions			
Min and max width	mm	567 - 761	567 - 761
Wheight with std wheels and cultivator included	Kg	255	255
Tyres			
Available tyres		6,5/80 - 12"	6,5/80 - 12"
		6,5/80 - 15"	6,5/80 - 15"
Adjustable rims for track regulation		yes	yes
Wheel axle with track width adjuster		-	-

Made in Italy



“GEARSTOP” does not turn the engine off but it locks the transmission and the PTO, in case of release of the handlebar grip.



A full bonnet covers the engine to protect the mechanical parts and to safeguard the operator from accidents.



Fixed hitch flange

passion



The external width of the wheels and the track width are adjustable, enabling the My Special to be adapted for work on specialized crops.



TABLE OF IMPLEMENTS AND ACCESSORIES

18



CULTIVATOR 19 &
CULTIVATOR 19S



LINKAGE 85



MOWING BAR
WITH SPECIAL TEETH



ONE-SPEED
BALLAST

TWIST 6



TWIST 9



TWIST 7S +



TWIST 9S



TWIST 12S



JOKER 8 DS



JOKER 10 DS



JOKER 12 S



JOKER 12S +



MY SPECIAL 14



MY SPECIAL 15



LINKAGE 70



CULTIVATOR 21M
& CULTIVATOR 21



CULTIVATOR 22
& CULTIVATOR 22M



GENERAL CATALOGUE

TWO-WHEELED TRACTORS



TRANSFER WHEEL



IMPLEMENT CARRIER



COULTER



TURN-WREST PLOUGH 90°



TURN-WREST PLOUGH 180°



COULTER FOR CULTIVATOR 19/21

•	•	•	•	•					•	•
•	•	•	•	•					•	•
•	•	•	•	•					•	
•	•	•	•	•					•	•
•	•	•	•	•					•	•
•	•	•	•	•					•	•
•	•	•	•	•					•	•
•	•	•	•	•					•	•
•										
•										

LAWN MOWER TP 60



SINGLE-SHARE PLOUGH



REAR CUTTER FOR CULTIVATOR 22



GRUBBER WITH 5 TINES



FRONT BALLAST

