








TE SERIE 1

SPECIFICHE TECNICHE

Modello Model	 (ton)	 (cm)	 (LxAxH cm)	 Kg	Cilindrata motore Motor displacement	 OIL (L/min)	 bar (min-max)	Trasmissione Transmission	Rotore Rotor	
TE1.1- 60 K/M	1.2-2.5	60	85x50x35	70	8-11	20-30	170-220	diretta direct	4 file 4 lines	12
TE2.1- 80 K/M	1.2-2.5	80	100x50x35	80	8-11	20-30	170-220	diretta direct	4 file 4 lines	16

K/M Rotor: - 4 Lines Rotor with austempered hammers and cutting blades interchangeable.

Professional Mulcher with 4 Lines Rotor with austempered hammers and cutting blades interchangeable, Direct transmission, Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation, gear motor



OMEF-GROUP S.R.L. unipersonale

Regione Bessiche 76/A
15070 Tagliolo Monferrato (AL)

Tel. +39 (0)143 1979459

Fax +39 (0)143 882429

Ufficio Commerciale: +39 349 8556830 | +39 328 672 1127

e-mail: info@omefgroup.com

Ufficio Commerciale: commercialeitalia@omefgroup.com